

TENCATE INDUSTRIAL FABRICS EUROPE

PRODUCT DATASHEET

MARKET SEGMENT : WATER MANAGEMENT

PRODUCT GROUP : NICOLON® WATER STORAGE LINERS

PRODUCT: NICOLON® C669/600 flex

CONSTRUCTION	Unit		Standard
Basic material fabric		PP	
Basic material coating		LDPE	
Colour		black	
Weight	gr/m²	600	EN 965
Thickness	micron	660	EN 964-1
MECHANICAL PROPERTIES			
Machine direction:			
Nominal tensile strength	N / 5cm	700	EN13859
Elongation at			
nominal tensile strength	%	22	EN 13859
Cross direction:			
Nominal tensile strength Elongation at	N / 5 cm	500	EN 13859
Nominal tensile strength	%	12	EN 13859
STANDARD ROLL AND PANE	L SIZES		
Roll length	m	400	
Roll width	m	3,05	
Maximum dimension panels	m²	4000	
Maximum width panels	m	50	
Maximum weight panels	kg	2000	

Disclaimer: TenCate assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. TenCate disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

