

TenCate Polyfelt® Accorder®

**The solution for soil stabilization
in public or residential areas.**



+ PRODUCT

**A PROVEN
SOLUTION FOR SOIL
STABILISATION**

- + For the build-up of well-draining soil structures**
- + Flexible structure**
- + High resistance and durability**

For any request, please contact us:

TENCATE GEOSYNTHETICS AUSTRIA GES.M.B.H.
Schachermayerstrasse 18
A - 4021 Linz - Austria
Phone: +43 732 6983 0 Fax: +43 732 6983 5353
Emailing: service.at@tencategeo.com
www.tencategeo.com

No more water runoff, puddles or ruts.
Driveways, patios, parking lots, garage entrances,
Car Parks, parks and gardens, golf courses,
Driveways and low-traffic roads...

Features

- Three-dimensional structure based on woven geotextile which greatly reduces rutting
- All types of filling materials can be used: sand, gravel, aggregates, expanded clay balls...
- Soil stabilization solution, constitutes a draining layer
- Lightweight and quick to install
Easy to handle, transport and cut
- Flexible, adapts to uneven floor surfaces, can be installed in curves and on slopes up to 15%
- No junction or stitching between walls and bottom
The cells are closed at the bottom
- Can be trafficked immediately with trucks, cars, wheelbarrows, wheelchairs, bikes and motorbikes...
- Durability > 50 years

Properties

Weight of a panel: +/- 50 kg
Cell size: 13 x 7 cm
Cell depth: 5,50 cm
Permissibility in water: 6 l/m²/s
Resistance of the geotextile to punching: 2,7 KN

Format & Packaging

Accorder® panel

- Folded panel = 5 x 1 m
- Unfolded panel = approx. 4,4 x 20m*

Foldable panel, easy to transport, if folded can be transported by car
*4.40m for a surface area of 90 to 100m² in function of stretching during the break

Accorder® ½ panel

- Folded panel in a box 65 x 28 x high 130cm
 - Unfolded panel = approx. 2,2 x 20m*
- *2.20m for a surface area of 40 to 50m² in function of stretching during the break

→ Find the installation manual on
www.tencategeo.com